

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Product name	QuelStop CE Marked Intumescent Acrylic Sealant
Product Code(s)	QSS310, QSS600
Revision Date	01/03/2025
Revision number	05



SECTION 1: Identification of the substance/mixture and of the company / undertaking

1.1 Product Identifier

Product form	Mixture
Product name	QuelStop CE Marked Intumescent Acrylic Sealant
Product Code	QSS310, QSS600
Type of Product	Adhesives, Sealant
Product group	Trade product
Colour	White

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Main use category	Professional use
Industrial/ Professional use spec	For professional use only
Use of the substance/ mixture	Adhesives, sealants

1.2.2 Uses advised against

No additional information available

1.3 Details of the supplier of the safety data sheet

Company Name	Quelfire Limited Unit 4 Spitfire Road Wardle Nantwich Cheshire CW5 6HT
Tel	0161 928 7308
Email	technical@quelfire.co.uk

1.4 Emergency Telephone Number

Emergency Telephone Number	(+44) 0161 928 7308
Language	English
Operating Hours	Monday – Friday 8am – 5pm GMT
Call 999 for Emergency. Call 111 for non-emergency medical advice	

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SECTION 2: Hazards Identification

2.1 Classification of the substance of mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]	Not Classified
Adverse physicochemical, human health and environmental effects	To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice

2.2 Label elements

Label according to Regulation (EC) No. 1272/2008 [CLP]	
EUH-statement	EUH205 - Contains epoxy constituents. May produce an allergic reaction. EUH208 - Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5), reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. EUH210 - Safety data sheet available on request.

2.3 Other Hazards

Other hazards which do not result in classification : Dust formation.

This substance/mixture does not meet the PBT criteria of UK REACH regulation, annex XIII Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with UK REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

MATERIAL SAFETY DATA:**QuelStop CE Marked Intumescent Acrylic Sealant**

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable

3.2 Mixtures

Name	Product Identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Calcium carbonate	(CAS-No.) 471-34-1 (EC-No.) 207-439-9	30 – 50	Not classified
Aluminium Hydroxide	(CAS-No) 21645-51-2 (EC-No) 244-492-7 (REACH No) 01-2119529246-39	10-30	Not classified
Titanium Dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (EC Index-No.) 022-006-00-2 (REACH-no) 01-2119489379-17	< 1	Carc. 2, H351
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	(CAS No) 2634-33-5 (EC No) 220-120-9 (EC index No) 613-088-00-6	0.008	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1)
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	(CAS No) 55965-84-9 (EC Index No) 613-167-00-5	0.001	Acute Tox. 2 (inhalation), H330 Acute Tox. 2 (dermal), H310 Acute Tox. 3 (Oral), H301 Skin Irrit. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)

Name	Product Identifier	specific Concentration limits
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	(CAS No) 2634-33-5 (EC No) 220-120-9 (EC index No) 613-088-00-6	(0.05 ≤C≤ 100) Skin sens. 1, H317
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	(CAS No) 55965-84-9 (EC Index No) 613-167-00-5	(0.0015 ≤C≤ 100) Skin sens. 1A, H317 (0.06 ≤C≤ 0.6) Skin Irrit. 2, H315 (0.06 ≤C≤ 0.6) Eye Irrit. 2, H319 (0.6 ≤C≤ 100) Skin Corr. 1C, H314 (0.6 ≤C≤ 100) Eye Dam. 1, H318

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Comments	Titanium dioxide Note 10 : The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.
----------	---

Full text of H- and EUH statements: see section 16

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SECTION 4: First aid measures

4.1 Description of first aid measures

General	If you feel unwell, seek medical advice
Skin contact	Wash skin with plenty of water
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses. If present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/ attention
Ingestion	Call a poison centre or a doctor if you feel unwell.
Inhalation	Remove person to fresh air and keep comfortable for breathing

4.2 Most important symptoms and effects, both acute and delayed

Symptoms/effects	Immediate effects can be expected after short term exposure.
Symptoms/ effects after skin contact	May cause slight irritation to the skin.
Symptoms/ effects after eye contact	May cause minor eye irritation
Symptoms/ effects after ingestion	May cause a light irritation of the linings of the mouth, throat, and gastrointestinal tract
Symptoms/ effects after inhalation	May cause minor irritation to the respiratory tract and to other mucous membranes

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SECTION 5: Fire-Fighting measures

5.1 Extinguishing media

Suitable Extinguishing Media

Water spray. Dry Powder. Foam. Carbon Dioxide

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire

Thermal decomposition generates: Carbon dioxide. Carbon monoxide. Toxic fumes may be released.

5.3 Advice for firefighters

Protection during firefighting

Do not attempt to take action without suitable protective equipment.
Self-contained breathing apparatus. Complete protective clothing.

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures

Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment

Do not attempt to take action without suitable protective equipment.
For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Ventilate spillage area. Shovel or sweep up and put in a closed container for disposal. Take up liquid spill into absorbent material. Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Prevent the product from entering drains or confined areas.

Other Information

Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements	Ensure good ventilation of the workstation. Wear personal protective equipment. Avoid dust formation.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Store in a well-ventilated place. Keep cool.
Incompatible products	Strong acids.

7.3. Specific end use(s)

No additional information available.

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Calcium carbonate (471-34-1)

United Kingdom - Occupational Exposure Limits

Local name	Calcium carbonate (Limestone, Marble)
WEL TWA (OEL TWA) [1]	10 mg/m ³ total inhalable 4 mg/m ³ respirable
WEL STEL (OEL STEL)	4 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Aluminium Hydroxide (21645-51-2)

United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) (1)	10 mg/m ³ total dust 4 mg/m ³ respirable dust
-----------------------	--

Titanium Dioxide (13463-67-7)

United Kingdom - Occupational Exposure Limits

Local name	Titanium dioxide
WEL TWA (OEL TWA) [1]	4 mg/m ³ respirable 10 mg/m ³ total inhalable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1 Appropriate engineering controls:

Ensure good ventilation of the workstation.

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

8.2.2 Personal protective equipment:

Dust formation: dust mask. Gloves

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Hand Protection

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves					EN ISO 374

Eye Protection

Safety glasses

Type	Field of application	Characteristics	Standard
Safety glasses			EN 166

Skin and body protection:

Wear suitable protective clothing

Personal protective equipment symbol(s):



8.2.3 Environmental exposure controls:

Avoid release to the environment

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Paste
Colour	White
Odour	Acrylic-like.
Odour Threshold	No Data Available
pH	5 - 9
Relative evaporation rate (butylacetate=1)	No Data Available
Melting point	Not applicable
Freezing point	No Data Available
Boiling point	No Data Available
Flash point	No Data Available
Auto-ignition temperature	No Data Available
Decomposition temperature	No Data Available
Flammability	Not applicable
Vapour pressure	No Data Available
Relative vapour density at 20°C	No Data Available
Relative density	No Data Available
Density	1.56 – 1.66 g/cm ³
Solubility	No Data Available
Partition coefficient n-octanol/ water (Log Pow)	No Data Available
Viscosity, Kinematic	No Data Available
Viscosity, dynamic	300000 – 900000 cP
Explosive properties	No Data Available
Oxidising properties	No Data Available
Explosive limits	No Data Available

9.2. Other information

No additional information available.

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (See section 7)

10.5. Incompatible materials

Oxidising agents. Strong acids

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition should not be produced.

MATERIAL SAFETY DATA:**QuelStop CE Marked Intumescent Acrylic Sealant**

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

Calcium carbonate (471-34-1)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)
LC50 inhalation rat	> 3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
pH	8.5 – 9.5
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Aspiration hazard	Not classified
Viscosity, kinematic	Not applicable

Aluminium Hydroxide (21645-51-2)	
LD50 oral rat	>2000 mg/kg bodyweight
LC50 inhalation rat	>2.3 mg/l
pH	9
NOAEL (animal/male, F0/P)	1000mg/kg bodyweight
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
Viscosity, kinematic	Not applicable

Titanium Dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity)
LC50 inhalation rat	> 6.8 mg/l/4h
pH	6 - 8
Skin corrosion/irritation	Not classified pH: 6.5 - 9
Serious eye damage/ Irritation	Not classified pH: 6.5 - 9
Respiratory or skin sensitisation	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

Based on available data, the classification criteria are not met

11.2.2. Other information

No additional information available

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SECTION 12: Ecological information

12.1. Toxicity

Ecology – general	The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short term (acute)	Not classified
Hazardous to the aquatic environment, long term (chronic)	Not classified
Not rapidly degradable	

Calcium carbonate (471-34-1)

LC50 - Fish [1]	> 10000
EC50 - Crustacea [1]	> 1000
EC50 72h - Algae [1]	> 200 mg/l

Titanium Dioxide (13463-67-7)

LC50 - Fish [1]	> 1000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l
EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Not potentially bioaccumulable

Calcium carbonate (471-34-1)

Partition coefficient n-octanol/water (Log Pow)	< 1
---	-----

12.4. Mobility in soil

Ecology - soil	Product adsorbs onto the soil. Liquid product : Readily absorbed into soil.
----------------	---

12.5. Results of PBT and vPvB assessment

This substance/ mixture does not meet the PBT criteria of REACH Regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



12.7. Other adverse effects

No additional information available

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	Disposal must be done according to official regulations.
Waste treatment methods	Dispose of contents/ container in accordance with licensed collector's sorting instructions
Additional information	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Packaging contaminated by the product: Disposal must be done according to official regulations. Non-contaminated packages may be recycled.
European List of Waste (LoW, EC 2000/532)	08 04 10 - waste adhesives and sealants other than those mentioned in 08 04 09

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SECTION 14: Disposal considerations

14.1. UN number

In accordance with ADR/ RID/ IMDG/ IATA/ ADN

ADR	Not Applicable
RID	Not Applicable
IMDG	Not Applicable
IATA	Not Applicable
ADN	Not Applicable

No supplementary information available

14.2. UN proper shipping name

In accordance with ADR/ RID/ IMDG/ IATA/ ADN

ADR	Not Applicable
RID	Not Applicable
IMDG	Not Applicable
IATA	Not Applicable
ADN	Not Applicable

No supplementary information available

14.3. Transport hazard class(es)

In accordance with ADR/ RID/ IMDG/ IATA/ ADN

ADR	Not Applicable
RID	Not Applicable
IMDG	Not Applicable
IATA	Not Applicable
ADN	Not Applicable

No supplementary information available

14.4. Packing group

In accordance with ADR/ RID/ IMDG/ IATA/ ADN

ADR	Not Applicable
RID	Not Applicable
IMDG	Not Applicable
IATA	Not Applicable
ADN	Not Applicable

No supplementary information available

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

14.5. Environmental hazards

In accordance with ADR/ RID/ IMDG/ IATA/ ADN

ADR	Not Applicable
RID	Not Applicable
IMDG	Not Applicable
IATA	Not Applicable
ADN	Not Applicable

No supplementary information available

14.6. Special precautions for user

Overland Transport	Not Applicable
Transport by sea	Not Applicable
Air transport	Not Applicable
Inland waterway transport	Not Applicable
Rail transport	Not Applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not Applicable

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)	Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)
REACH Annex XIV (Authorisation List)	Contains no substance(s) listed on REACH Annex XIV (Authorisation List)
REACH Candidate List (SVHC)	Contains no substance(s) listed on the REACH Candidate List
PIC Regulation (Prior Informed Consent)	Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)
POP Regulation (Persistent Organic Pollutants)	Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)
Ozone Regulation (1005/2009)	Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)
Explosives Precursors Regulation (2019/1148)	Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)
Drug Precursors Regulation (273/2004)	Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out for the substance or the mixture by the supplier

MATERIAL SAFETY DATA:**QuelStop CE Marked Intumescent Acrylic Sealant**

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
1.2	Additional information	Modified	Modification of use descriptor
2.2	EUH-statements	Added	EUH205 Added
2.3	Additional information	Added	Added information regarding dust formation
3.2	Composition/information on ingredients	Added	Added information regarding isothiazolinones and Titanium dioxide
4.2	Symptoms/effects after eye contact	Modified	
4.2	Symptoms/effects after ingestion	Modified	
4.2	Symptoms/effects after skin contact	Modified	
5.2	Additional information	Added	Added information regarding pyrolysis products
6.3	Additional information	Added	Added information regarding the disposal of solid spills
8.1	Additional information	Added	Titanium Dioxide WELs added
8.2	Additional information	Added	Added required EN standards for PPE
12.4	Mobility in soil	Modified	Added information regarding liquid product being absorbed into soil
13.1	Additional information	Modified	EU LoW code and additional disposal information

Abbreviations and acronyms	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of dangerous goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological Limit Value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect Level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community Number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

MATERIAL SAFETY DATA:

QuelStop CE Marked Intumescent Acrylic Sealant

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Abbreviations and acronyms	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Full Text of H- and EUH- statement	
Acute Tox. 2 (Dermal)	Acute toxicity (Dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (Inhalation), Category 2
Acute Tox. 3 (Oral)	Acute toxicity (Oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (Oral), Category 4
Aquatic Acute 1	Hazardous to aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to aquatic environment – Chronic Hazard, Category 2
EUH205	Contains epoxy constituents. May produce an allergic reaction.
EUH208	Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one(2634-33-5), reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/ eye irritation, category 1
Eye Irrit. 2	Serious eye damage/ eye irritation, category 2
Repr. 2	Reproductive toxicity, Category 2
H301	Toxic if swallowed
H302	Harmful if swallowed
H310	Fatal in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
Skin Corr. 1C	Skin corrosion/ irritation, Category 1, sub-category 1C
Skin Irrit. 2	Skin corrosion/ irritation, Category 2
Skin sens. 1	Skin sensitisation, Category 1
Skin sens. 1A	Skin sensitisation, Category 1A

The above information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.