

DECLARATION OF PERFORMANCE:

QuelStop Acrylic Sealant

According to Annex III of Regulation (EU) Nr. 305/2011 (Construction Products Regulation)

Product name	QuelStop Acrylic Sealant	
Product Code(s)	QSS310, QSS600	
Revision Date	01/04/2025	
Revision number	03	

Section 1: Unique identification code of the product-type

QuelStop HPE Sealant

Section 2: Type, batch or serial number as required pursuant to Article 11(4)

See batch number displayed on the product

Section 3: Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification

Fire stopping and sealing product for linear joint & gap seals, see ETA 20/1057

Fire stopping and sealing Product for Penetration Seals, see ETA 20/1058

Linear Joint & Gap Seals	Horizontal & vertical linear joints in flexible wall constructions	The field of application has to comply with the content of the related ETA 20/1057
Linear Joint & Gap Seals	Horizontal & vertical linear joints in rigid wall constructions, rigid floor constructions, steel constructions & wood constructions	The field of application has to comply with the content of the related ETA 20/1057
Cable penetrations	Insulated & non insulated, cables, cable trays & cable ladders	The field of application has to comply with the content of the related ETA 20/1058
Pipe penetrations	Insulated & non insulated metal pipes	The field of application has to comply with the content of the related ETA 20/1058

Section 4: Name, registered trade name or registered trademark and contact address as required pursuant to Article 11(5)

Company Name	Quelfire Limited Unit 4 Spitfire Road Wardle Nantwich Cheshire CW5 6HT
Tel	0161 928 7308
Email	technical@quelfire.co.uk

Section 5: Authorised representative:

Company Name	Certification Company B.V. Veluwezoom 42 1327 AH Almere The Netherlands
Email	admin@certification-company.com

Section 6: System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1

DECLARATION OF PERFORMANCE:

QuelStop Acrylic Sealant

According to Annex III of Regulation (EU) Nr. 305/2011 (Construction Products Regulation)

Section 7: Harmonised standard

N/A

Section 8: In the case of the declaration of performance concerning product covered by a Harmonised Standard and/or ETA:

Warrington Certification Ltd issued ETA Number 20/1057 & 20/1058 on the basis of Guideline for European Technical Approval of Fire Stopping and Fire Sealing Products: EAD 350454-00-1104 Issue September 2017 performed initial and continuous surveillance of the place of manufacture and the factory production control implemented, sampled product and witnessed initial type testing under system 1.


UL international UK Ltd have performed surveillance of the place of manufacture and the factory production control implemented issued the Certificate of Constancy of Performance 2531-CPR-CXO10342 & 2531-CPR-CXO10343

Section 9: Declared performance:

Essential Characteristic	Declared performance/ Harmonised technical specification
Reaction to fire	Class F according to EN 13501-1 see ETA 20/1057 Class F according to EN 13501-1 see ETA 20/1058
Resistance to fire	Resistance to fire performance and field application in accordance with EN 13501-2 see ETA 20/1057 Resistance to fire performance and field application in accordance with EN 13501-2 see ETA 20/1058
Air Permeability	Tested in accordance with BS EN1314-1, see ETA 20/1057 Tested in accordance with BS EN1314-1, see ETA 20/1058
Dangerous substances	See ETA 20/1057 See ETA 20/1058
Airbourne Sound Insulation	Tested in accordance with EN ISO 10140-2:2010 & EN ISO 140-3 & EN ISO 717-1, see ETA 20/057 Rw (C;Ctr) 38(-2;-7) Tested in accordance with EN ISO 10140-2:2010 & EN ISO 140-3 & EN ISO 717-1, see ETA 20/058 Rw (C;Ctr) 38(-2;-7)
Durability and serviceability	Z ¹ (0/+40°C) intended for use at internal conditions with high humidity (85%) in accordance with EOTA Technical Report – TR024 See ETA 20/1057 Z ¹ (0/+40°C) intended for use at internal conditions with high humidity (85%) in accordance with EOTA Technical Report – TR024 See ETA 20/1057, Clause 3.4.1
Movement Capability	≤7.5% see ETA 20/1057 ≤7.5% see ETA 20/1058

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer.

	
Keith Wells	Darryl Wells
Managing Director Quelfire Ltd	Product Development Quelfire Ltd